

# ClearChart<sup>®</sup>2 Digital Acuity System

Smart, easy acuity.





## ClearChart<sup>®</sup>2 Digital Acuity System



The Reichert<sup>®</sup> **ClearChart<sup>®</sup> 2** Digital Acuity System is uniquely designed to meet all of your acuity testing needs. This all-in-one system is sleek, attractive and simple to use. Separate components or software are not required to use the device. Simply mount on the wall, plug in and start testing.

ClearChart 2 features a 19 inch, high resolution, LED backlit display that is lightweight, cool running and long-lasting. The system is free of fans and hard drives, providing quiet and dependable operation in the exam room. A custom designed LINUX operating system ensures consistent and reliable software performance. The infrared remote control enables access to all tests from virtually anywhere in the room.

## Now, add your own videos and image files:

ClearChart 2 now has the capability of importing additional videos and image files to customize the system to your needs. Simply import the files from a USB drive. Enhance your patients' experience with more information to provide clinical education and make them aware of all of your services.

#### **ClearChart 2 features:**

- Configure for direct or mirrored viewing
- Large range of optotypes: 17 letter set, 8 letter set, Sloan, HOTV, Landolt C, Landolt C and O, Tumbling E
- Children's Optotypes: three different sets including Allen Symbols, Kolt-like symbols and other images
- Random sequencing of optotypes
- Special Test Charts for astigmatism testing, suppression and fixation
- Contrast Sensitivity testing with sine-wave grating or contrast optotypes
- Complies with ETDRS protocol
- Adjustable red/green for compatibility with any refraction system
- Cartoon loop with sound for pediatric fixation
- Patient education slides
- Integrates with the Reichert Auto Phoroptor RS®

ClearChart 2 enhances the acuity testing and refraction experience for both you and your patient. The bright, high-contrast display enables procedures to be performed with the lights on or off. The easy-to-use remote allows the examiner to switch exam screens, exam modes and access slides to help educate your patients.



Snellen Chart





**Contrast Sensitivity** 



Pediatric Fixation

### **Specifications**

ÓÓĆĆ

Catalog Number	13760 - ClearChart 2 with Wall Mount
Display	19 inches (48.26 cm) LCD
Max Illumination	220 cd/m <sup>2</sup>
Photopic Illumination	85 cd/m <sup>2</sup>
Mesopic Illumination	3 cd/m <sup>2</sup>
Height	16.91 inches (42.95 cm)
Width	19.88 inches (50.49 cm)
Depth	3.25 inches (8.26 cm)
Weight (unpacked)	10 lbs. (4.5 kg)
Power Requirements	100-240 volts AC, 50/60 Hz, 70-95 VA
Fuses	T3.15AL250
Refraction Range	6 ft (1.83 m) - 31 ft (9.5 m)



are. Preserving signi.

ISO 9001 Certified

Reichert, Inc. 3362 Walden Avenue, Depew, NY 14043 Toll Free: 888-849-8955 • Tel: (716) 686-4500 Fax: (716) 686-4545 • www.reichert.com

Reichert products are designed and manufactured under quality processes meeting ISO 9001 requirements

# ULTRA PRECISION TECHNOLOGI

Proudly Made in the USA.

Visit www.reichert.com or contact your Authorized Reichert Technologies Distributor.

Important Notice: For your own protection, purchase instruments from and have them serviced only by Reichert Technologies or an Authorized Reichert Technologies Distributor.

13760-110-Rev-B ©2013 AMETEK, Inc. All rights reserved. - Specifications subject to change without notic Reichert and Reichert Technologies are registered trademarks of Reichert, Inc. "Advancing Eye Care. Preserving Sight." is a trademark of Reichert, Inc. AMETEK is a registered trademark of AMETEK, Inc.