

Isotemp®

F Fisher Scientific

Isotemp General Purpose
Refrigerators and Freezers



Reliable and Secure for Total Peace of Mind

Isotemp General Purpose Refrigerators and Freezers

Reliable, safe cold storage

Introducing the Isotemp* General Purpose Refrigerators and Freezers

Our complete line of General Purpose Refrigerators and Freezers provides the reliability and security essential for the protection of sensitive lab samples in +4° and -30°C models.

Reliable Sample Protection and Storage

All models of our Isotemp General Purpose range deliver the performance, security and quality features you have come to depend on from us.

- Wide range of capacities — from 12 to 72 cu. ft.
- Exceptional security features
- Outstanding temperature stability
- Intuitive digital controls
- Quality, robust construction



34 cu. ft. Lab Freezer,
Cat. No. 11-670-204

27 cu. ft. Lab Refrigerator with
Stainless-Steel Interior and
Door, Cat. No. 11-670-242

12 cu. ft. Lab Refrigerator
with Glass Door,
Cat. No. 11-670-226



49 cu. ft. Lab Refrigerator with Stainless-Steel Doors
and Chart Recorder, Cat. No. 11-670-252



72 cu. ft. Lab Refrigerator with Glass Doors, Cat. No. 11-670-260

Isotemp General Purpose Refrigerators and Freezers

Reliable, safe cold storage



Our Isotemp General Purpose Refrigerators and Freezers offer the dependability and safety required for your daily lab applications.*

- » Range of sizes to suit your lab space and needs
- » Choice of painted or stainless-steel interior finish (refrigerators only)
- » Available with and without chart recorders

Performance.

- » Refrigerator cabinet temperature range: 1° to 12°C (factory setpoint 4°C)
- » Freezer cabinet temperature range: -12° to -30°C (factory setpoint -30°C)
- » Excellent temperature stability of $\pm 3^{\circ}\text{C}$
- » Digital temperature controller with intuitive interface
- » High-density, fluorine-free insulation
- » Automatic defrost

Security.

- » Keyed ON/OFF switch
- » Chart recorder (optional)
- » Control panel with key lock
- » High and low temperature visual and audio alarms
- » Lockable doors
- » Easily accessible contacts for backup monitoring
- » Door Ajar Alarm (except sliding glass doors)

Quality.

- » Choice of solid or glass doors (refrigerators only)
- » Optional dual-pane glass doors (refrigerator models)
- » Painted, high-quality steel exterior
- » Choice of painted or stainless-steel interior (refrigerators only)
- » Casters for easy mobility with leveling for better stability
- » Quiet refrigeration system
- » Standard 1" rear access port

Note: Models only available in North America.

Warranty: 13 months parts and labor plus additional four-year compressor (parts only)

Certifications: UL listed



Isotemp General Purpose Refrigerators and Freezers

Reliable, safe cold storage

Fisher Scientific* Isotemp* General Purpose Series Lab Refrigerators

Reliable cold storage for general purpose applications

- Capacities from 12 cu. ft. to 72 cu. ft.
- Range of sizes: from single-door to large capacity, three-door uprights
- Choice of painted or stainless-steel interiors
- Available with or without chart recorders

Performance

- Refrigerator cabinet temperature range: 1° to 12°C (factory setpoint 4°C)
- Digital temperature controller with intuitive interface
- Excellent temperature stability of $\pm 3^{\circ}\text{C}$
- High-density, fluorine-free insulation
- Automatic defrost

Security

- Keyed ON/OFF switch
- Optional chart recorder

- High/low temperature, visual/audio alarms
- Choice of solid or glass lockable doors
- Easily accessible contacts for backup monitoring
- Door ajar alarm (except sliding glass doors)
- Control panel with key lock

Quality

- Dual-pane glass or stainless-steel doors
- High-quality painted steel exterior
- Choice of painted or stainless-steel interior
- Casters for easy mobility with leveling for better stability
- Quiet refrigeration system
- Standard 1" rear access port

Specifications and Ordering Information

Capacity	Interior D × W × H	Exterior L × W × H*	Monitoring Options	Door(s)/Shelves	Electrical Requirements	Weight	Cat. No.						
Gray painted exterior with stainless-steel liner													
23 cu. ft.	28.5×24×61.75"	32×27×78" (Add 1¼" to depth for handle)	Alarms Only	Glass door, single/Gray – 4 Wire	115V 60Hz; 5-15P; 5.8A	300 lb.	11-670-232						
			Alarms and Recorder	Solid stainless-steel door, single/Gray – 4 Wire			11-670-233						
			Alarms Only				11-670-234						
			Alarms and Recorder				11-670-235						
27 cu. ft.	28.5×27×61.75"	32×30×78" (Add 1¼" to depth for handle)	Alarms Only	Glass door, single/Gray – 4 Wire	115V 60Hz; 5-15P; 5.8A	386 lb.	11-670-240						
			Alarms and Recorder	Solid stainless-steel door, single/Gray – 4 Wire			11-670-241						
			Alarms Only				11-670-242						
			Alarms and Recorder				11-670-243						
45 cu. ft.	27×48.63×61.75"	32×52×78"	Alarms Only	Sliding glass door, double/Gray – 8 Wire	115V 60Hz; 5-15P; 8.8A	561 lb.	11-670-248						
			Alarms and Recorder				11-670-249						
			49 cu. ft.				28.5×48.63×61.75"	32×52×78" (Add 1¼" to depth for handle)	Alarms Only	Glass door, double/Gray – 8 Wire	115V 60Hz; 5-15P; 8.8A	597 lb.	11-670-254
									Alarms and Recorder	Solid stainless-steel door, double/Gray – 8 Wire			11-670-255
Alarms Only	11-670-256												
Alarms and Recorder	11-670-257												
72 cu. ft.	28.5×72×61.75"	32×75×78" (Add 1¼" to depth for handle)	Alarms Only	Glass door, triple/Gray – 12 Wire	115V 60Hz; 5-15P; 9.9A	730 lb.	11-670-260						
			Alarms and Recorder				11-670-261						
			White painted exterior with white liner										
			12 cu. ft.				20.75×21×45.75"	24×24×62"	Alarms Only	Glass door, single/White – 4 Wire	115V 60Hz; 5-15P; 5A	230 lb.	11-670-226
Alarms and Recorder	11-670-227												
23 cu. ft.	28.5×24×61.75"	32×27×78"		Alarms Only	Glass door, single/White – 4 Wire	115V 60Hz; 5-15P; 5.8A			300 lb.				11-670-228
				Alarms and Recorder	Solid stainless-steel door, single/White – 4 Wire								11-670-229
			Alarms Only	11-670-230									
			Alarms and Recorder	11-670-231									
27 cu. ft.	28.5×27×61.75"	32×30×78"	Alarms Only	Glass door, single/White – 4 Wire	115V 60Hz; 5-15P; 5.8A	386 lb.	11-670-236						
			Alarms and Recorder	Solid stainless-steel door, single/White – 4 Wire			11-670-237						
			Alarms Only				11-670-238						
			Alarms and Recorder				11-670-239						
38 cu. ft.	27×40.5×61.75"	32×43.5×78"	Alarms Only	Sliding glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A	524 lb.	11-670-244						
			Alarms and Recorder				11-670-245						
			45 cu. ft.				27×48.63×61.75"	32×52×78"	Alarms Only	Sliding glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A	561 lb.	11-670-246
									Alarms and Recorder				11-670-247
49 cu. ft.	28.5×48.63×61.75"	32×52×78"		Alarms Only	Glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A			597 lb.				11-670-250
				Alarms and Recorder	Solid stainless-steel door, double/White – 8 Wire								11-670-251
			Alarms Only	11-670-252									
			Alarms and Recorder	11-670-253									
72 cu. ft.	28.5×72×61.75"	32×75×78"	Alarms Only	Glass door, triple/White – 12 Wire	115V 60Hz; 5-15P; 9.9A	730 lb.	11-670-258						
			Alarms and Recorder				11-670-259						
			23 cu. ft.				28.5×24×61.75"	32×27×78"	Alarms Only	Glass door, single/White – 4 Wire	115V 60Hz; 5-15P; 5.8A	300 lb.	11-670-226
									Alarms and Recorder				11-670-227
Alarms Only	11-670-228												
Alarms and Recorder	11-670-229												

* Add 3" exterior height when using provided standard casters.

Isotemp General Purpose Refrigerators and Freezers

Reliable, safe cold storage



Fisher Scientific* Isotemp* General Purpose Series Lab Freezers

Reliable cold storage for general purpose applications

- Capacities from 24 cu. ft. to 48 cu. ft.
- Available with or without chart recorders

Performance

- Freezer cabinet temperature range: -12° to -30°C (factory setpoint -30°C)
- Digital temperature controller with intuitive interface
- Excellent temperature stability of $\pm 3^{\circ}\text{C}$
- High-density, fluorine-free insulation
- Automatic defrost

Security

- Keyed ON/OFF switch
- Optional chart recorder
- High/low temperature, visual/audio alarms
- Lockable doors
- Easily accessible contacts for backup monitoring
- Door ajar alarm
- Control panel with key lock

Quality

- Durable, stainless-steel doors
- High-quality steel exterior
- Stainless-steel interior
- Casters for easy mobility with leveling for better stability
- Quiet refrigeration system
- Standard 1" rear access port



24 cu. ft. Lab Freezer without Chart Recorder,
Cat. No. 11-670-202

Specifications and Ordering Information

Capacity	Interior D x W x H	Exterior L x W x H*	Monitoring Options	Door[s]/Shelves	Electrical Requirements	Weight	Cat. No
24 cu. ft.	28×22×60"	32×26×78.5" (Add 1¾" to depth for handle)	Alarms Only Alarms and Recorder	Solid stainless-steel door, single/Gray – 3 Wire	115V 60Hz, 5-15P, 9.7A	392 lb.	11-670-202 11-670-203
34 cu. ft.	28×31×60"	32×35×78.5" (Add 1¾" to depth for handle)	Alarms Only Alarms and Recorder	Solid stainless-steel door, single/Gray – 3 Wire	115V 60Hz, 5-15P, 10.4A	429 lb.	11-670-204 11-670-205
48 cu. ft.	28×48×60"	32×52×78.5" (Add 1¾" to depth for handle)	Alarms Only Alarms and Recorder	Solid stainless-steel door, double/Gray – 6 Wire	208-230V 60Hz, L14-20, 7.6A	630 lb.	11-670-206 11-670-207

* Add 3" exterior height when using provided standard casters.

Isotemp General Purpose Chromatography Refrigerators

Reliable, safe cold storage

Fisher Scientific* Isotemp* General Purpose Series Chromatography Refrigerators

Secure storage for chromatography applications

- Capacities from 27 cu. ft. to 72 cu. ft.
- Range of sizes: from single-door to large capacity, three-door uprights
- Choice of painted or stainless-steel interior finish

Performance

- Refrigerator cabinet temperature range: 1° to 12°C (factory setpoint 4°C)
- Excellent temperature stability of $\pm 3^{\circ}\text{C}$
- Bright digital display
- Automatic defrost

Security

- High/low temperature audio and visual alarms
- Chart recorder (optional)
- Keyed ON/OFF switch
- Door ajar alarm (except sliding door models)

Quality

- High-quality painted steel exterior
- Two 2" side access ports
- Energy-efficient, double pane, argon-filled glass doors
- Interior duplex outlet



27 cu. ft. Chromatography Refrigerator,
Cat. No. 11-670-210

Specifications and Ordering Information

Capacity	Interior D x W x H	Exterior D x W x H*	Monitoring Options	Door(s)/Shelves	Electrical Requirements	Weight	Cat. No.
Stainless-steel cabinet with stainless-steel liner							
27 cu. ft.	28.5x27x61.75"	32x30x78" (Add 1 1/4" to depth for handle)	Alarms Only Alarms and Recorder	Glass door, single/Gray – 4 Wire	115V 60Hz; 5-15P; 5.8A	300 lb.	11-670-210 11-670-211
45 cu. ft.	27x48.63x61.75"	32x52x78"	Alarms Only Alarms and Recorder	Sliding glass door, double/Gray – 8 Wire	115V 60Hz; 5-15P; 8.8A	561 lb.	11-670-216 11-670-217
49 cu. ft.	28.5x48.63x61.75"	32x52x78" (Add 1 1/4" to depth for handle)	Alarms Only Alarms and Recorder	Glass door, double/Gray – 8 Wire	115V 60Hz; 5-15P; 8.8A	597 lb.	11-670-220 11-670-221
72 cu. ft.	28.5x72x61.75"	32x75x78" (Add 1 1/4" to depth for handle)	Alarms Only Alarms and Recorder	Glass door, triple/Gray – 12 Wire	115V 60Hz; 5-20P; 9.9A	730 lb.	11-670-224 11-670-225
White painted cabinet with white liner							
27 cu. ft.	28.5x27x61.75"	32x30x78"	Alarms Only Alarms and Recorder	Glass door, single/White – 4 Wire	115V 60Hz; 5-15P; 5.8A	300 lb.	11-670-208 11-670-209
38 cu. ft.	27x40.5x61.75"	32x43.5x78"	Alarms Only Alarms and Recorder	Sliding glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A	524 lb.	11-670-212 11-670-213
45 cu. ft.	27x48.63x61.75"	32x52x78"	Alarms Only Alarms and Recorder	Sliding glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A	561 lb.	11-670-214 11-670-215
49 cu. ft.	28.5x48.63x61.75"	32x52x78"	Alarms Only Alarms and Recorder	Glass door, double/White – 8 Wire	115V 60Hz; 5-15P; 8.8A	597 lb.	11-670-218 11-670-219
72 cu. ft.	28.5x72x61.75"	32x75x78"	Alarms Only Alarms and Recorder	Glass door, triple/White – 12 Wire	115V 60Hz; 5-20P; 9.9A	730 lb.	11-670-222 11-670-223

* Add 3" exterior height when using provided standard casters.

Isotemp General Purpose Chromatography Refrigerators

Reliable, safe cold storage



Interior Side Access Port



Backwall Plug

*45 cu. ft. Chromatography Refrigerator,
Cat. No. 11-670-214*

Isotemp®

Isotemp General Purpose
Refrigerators and Freezers



Fisher Scientific

Part of Thermo Fisher Scientific

In the United States:

For customer service, call 1-800-766-7000.

To fax an order, use 1-800-926-1166.

To order online: www.fishersci.com

©2011 Thermo Fisher Scientific Inc. All rights reserved.

*Trademark. For ownership, go to www.fishersci.com/trademarks.

Litho in the U.S.A.

11_3827

JJ/AD_5/11

In Canada:

For customer service, call 1-800-234-7437.

To fax an order, use 1-800-463-2996.

To order online: www.fishersci.ca

BRCISISOGP 0611
BN0517111