ORDERING INFORMATION

| Order no. | Description | Price [€] |
|-----------|--|-----------|
| 1808-0506 | BioShake iQ | 1,850€ |
| | | |
| | ACCESSORIES | |
| | Thermo adapter for microplates & PCR plates | |
| 1808-1021 | Adapter for microplate . Flat bottom standard | 250€ |
| 1808-1022 | Adapter for microplate . Flat bottom High Base | 250€ |
| 1808-1031 | Adapter for microplate . 96 well round bottom, type 1 . Corning® #3367, #3789 | 350€ |
| 1808-1032 | Adapter for microplate . 96 well round bottom, type 2 . Greiner®, NUNC®, Matrix® plates | 350€ |
| 1808-1041 | Adapter for PCR Plate . Eppendorf® 96 well . #0030-128.672 | 450€ |
| 1808-1051 | Adapter for PCR Plate . Eppendorf® 384 well . #0030-128.532 | 450€ |
| | Thermo adapter for deep well & storage plates | |
| 1808-1121 | Adapter for Deep Well Plate . Eppendorf® 96/1000 µl . #0030-503.209 | 450€ |
| 1808-1131 | Adapter for Deep Well Plate . Eppendorf® 96/500 µl . #0030-501.101 | 450€ |
| 1808-1141 | Adapter for Deep Well Plate . BRAND® 96/1100 µl . #701350 | 450€ |
| 1808-1151 | Adapter for Deep Well Plate . NUNC® 96/2000 µl . #278752 | 450€ |
| 1808-1161 | Adapter for Deep Well Plate . Axygen® 96/0.6 ml V-bottom . #P-DW-500-C | 450€ |
| 1808-1162 | Adapter for Deep Well Plate . Axygen® 96/2.0 ml round bottom . #P-DW-20-C | 450€ |
| 1808-1171 | Adapter for Abgene® 96/2.2 ml, square well storage plate . #AB-09032 | 450€ |
| 1808-1172 | Adapter for Abgene® 96/0.8 ml, round well storage plate . #AB-0765, #AB-0859 | 450€ |
| | Thermo adapter for centrifuge tubes | |
| 1808-1060 | Adapter for tubes . 15x 5.0 ml | 350€ |
| 1808-1061 | Adapter for tubes . 24x 2.0 ml or 15x 0.5 ml | 350€ |
| 1808-1062 | Adapter for tubes . 24x 1.5 ml or 15x 0.5 ml | 350€ |
| 1808-1063 | Adapter for tubes . 40x 0.5 ml or 28x 0.2 ml | 350€ |
| 1808-1064 | Adapter for tubes . 96x 0.2 ml | 350€ |
| 1808-1093 | Adapter for FALCON® tubes . 4x 50 ml or 2x 15 ml | 450€ |
| 1808-1094 | Adapter for FALCON® tubes . 12x 15 ml | 450€ |
| | Thermo adapter for glass vials | |
| 1808-1069 | Adapter for glass vials . 35x 2.0 ml, Ø 10.8 mm | 350€ |
| 1808-1071 | Adapter for glass vials . 30x 2.0 ml, Ø 12 mm | 350€ |
| 1808-1072 | Adapter for glass vials . 20x 4.0 ml, Ø 15 mm | 350€ |
| 1808-1073 | Adapter for glass vials . 20x 4.0 ml, Ø 17 mm | 350€ |
| 1808-1074 | Adapter for glass vials . 20x 6.0 ml, Ø 19 mm | 350€ |
| | Thermo adapter for Alere™ | |
| 1808-1081 | Adapter for Alere™ ArrayStrip (5 stripes, incl. passive heating-cover and cooling-cover) | 550€ |
| 1808-1085 | Adapter for 24x Alere™ ArrayTube 1.5 ml | 350€ |
| 1808-1023 | Adapter for Alere™ ArrayStrip, flat bottom (12 stripes, for using with standard frame) | 250€ |
| | | |
| | Customized adapters are available on request | |

Legal Notices & Trademarks

QInstruments is owner of numerous patents worldwide. Please respect our intellectual proper

WO2008135565, US823588, EP2144716: Sample handling device for and methods of handling a sample WO2011113858, US9126162, EP2547431: Positioning unit for a functional unit

WO2013113847, US10052598, EP2809436: Cog-based mechanism for generating an orbital shaking motion WO2013113847, US9371889, EP2809435: Mechanism for generating an orbital motion or a rotation motion by inversing a drive direction of a drive unit

WO2014207243, US20160368003, EP3013480: Application-specific sample processing by modules surrounding a rotor mechanism for sample mixing and sample separatio

Please notify us in writing, by email or mail to our designated agent, if you believe that a user has infringed our intellectual property right

te

QInstruments trademarks are recognised worldwide. Please respect our trademarks as we will vigorously protect their proper usage. BioShake® (QInstruments GmbH)

Trademarks of third parties may appear on this site when referring to those entities or their products or services. All registered names, trademarks, etc. used on this site, even when not specifically marked as such, are not to be considered unprotected by law. Any names and trademarks not specifically marked or listed are property of the respective owner

Technical specifications are subject to change without notice.

QInstruments GmbH

Loebstedter Strasse 101 07749 Jena . Germany

+49 3641 876120

email info@QInstruments.com

QInstruments.com web

BioShake iQ

High-end thermoshaker for microplates & tubes

Recommended for use in the daily laboratory routine

HIGHLIGHTS

- For all microplates, tubes and glass vials
- Fast mixing from 200 up to 3,000 rpm
- High-precision heating from ambient to 99°C
- Programmable
- Integrated timer and short mix function
- Stylish, fire resistant **aluminium** housing
- Wide range of adapters and blocks







INTRODUCTION

A scientific innovation for laboratories

throughput.

Gentle mixing of samples by planar orbital motion

German designed and manufactured, BioShake iQ thermoshaker offer an ultra-efficient, 2-dimensional shaking axis so that samples mix completely in a fraction of the time of competing systems. The mixing orbit of 2.0 mm is always constant. The orbital shaking is precisely controlled, in fact, that you need never spin down your plates after mixing. Even tubes, vials, high density plates, or low sample volumes, offer no obstacle for these precision tools. Fully adjustable between 200 rpm and 3,000 rpm, well beyond the speeds of most other brands, guarantees fast, splatter-free, mixing for tubes, glass vials or across an entire 384-well microplate.

Homogeneous and accurate temperature control

Within the BioShake iQ thinnest, large-area heating elements and sensors are integrated. The heat output of 75 W can be adjusted seamlessly from room temperature to 99°C. The equipment is fitted with a new and very reliable electronic temperature control which ensuring optimum warming of samples. During the heat up time the special electronic control system guarantees the same temperature for all vessels with minimal deviations. Precisely machined adapter plates allow an individual adaptation to the used sample holder.

Stylish aluminium housing

The first-class finished aluminium housing gives the BioShake iQ its essential functionality. It provides a high amount of security, device stability and ensures a long service life.





Compact and stylish designed, the BioShake iQ high-speed thermoshaker lets you perform all your standard runs with a minimum of adjustments, and offers outstanding performance to handle a wide range of applications across biotechnology, pharmaceutical and academic research.

By combining the mixing operation with the incubation phase, reaction process times and operator workload are reduced and efficiency of many procedures is increased, resulting in a higher

TECHNICAL SPECIFICATIONS



| Adapter Plates | |
|--------------------------------------|---|
| Microplates | 96-, 384-,1536-well microplates (flat bottom, PCR, deep well, v-well, square-well and u-well shape) |
| Tubes | 0.2 / 0.5 / 1.5 / 2.0 ml standard microfuge tubes |
| Glass vials | Glass vials 2-6 ml with Ø12, Ø15, Ø17, Ø19 mm |
| Temperature | |
| Temperature range | Heating from ambient to 99°C |
| Temperature setting | from 0°C to 99°C / 0.5°C increments |
| Temperature accuracy | ±0.5°C at 45°C / ±1.0°C at 95°C |
| Heat-up time | 10 min from ambient to 95°C (ca. 7°C/min), no active cooling |
| Mixing | |
| Mixing frequency | Microplates: 200-3,000 rpm, Tubes: 200-1,800 rpm, Vials: 200-1,800 rpm |
| Mixing orbit | constant 2.0 mm diameter |
| Speed setting resolution | 50 rpm increments |
| Mixing regulation accuracy | ± 25 rpm |
| Short-Mix function | Yes |
| Timer | |
| Timer setting | 1 min - 99 h / with automatic switch to stand-by |
| Working / Alarm | Continuous working / Audible alarm |
| Programming | |
| Programs / Definable buttons | 2 programs / Definable buttons P1 and P2 |
| Individual program capacity / Memory | 3 steps / Internal memory |
| Display | |
| Display | 2x 16 digits LCD-display with backlight (blue) |
| Target values / Actual values | Time, Mixing frequency, Temperature |
| Electrical | |
| Operating Voltages | 24 V DC input / 120 Watt |
| Power supply | External power supply unit / 100-240 V AC, 50-60 Hz |
| Properties | |
| Housing Material | Aluminum anodized |
| Environment operating range | +5°C to 45°C (80 % max. relative humidity) |
| Dimensions (W x D x H) | 142 mm x 170 mm x 80 mm |
| Weight | 2.7 kg |

CHANGEABLE THERMO ADAPTER PLATES

A variety of standardized thermo adapter plates

For all BioShake units Q.Instruments offers high precision adapter plates to allow a perfect fit for all kinds of standard tubes, vials, microplates and other different disposables. The adapter plates are optimized for an excellent heat transfer to the disposables and enhance the uniformity over all wells and the heat up or cool down time. The exchange of adapter plates can be performed very easily within one minute.



SCOPE OF DELIVERY

- 1x BioShake iQ
- 1x Power supply 110-240 VAC, 50-60 Hz, 24 VDC
- 2x Power cords US & EU/DE
- 1x Calibration certificate •
- 1x Documentation
- 1x Adapter for microplate flat bottom (1808-1021)

www.QInstruments.com

Order no. 1808-0506

Free delivery worldwide 2 year full warranty Expert support



Order no. 1808-1511

Order no. 1808-1521