

®

Clarke

## ***OBS 18 & OBS 18DC*** Orbital Floor Sanders



[www.americansanders.com](http://www.americansanders.com)


**Clarke®**  
**American Sanders**

*Because Pride Still Matters.*

# OBS 18 & OBS 18DC

## Orbital Floor Sander

# Clarke® American Sanders



### KEY FEATURES

- Powerful totally enclosed motor requires less maintenance
- Rigid cast aluminum pad driver provides increased durability
- Designed specifically for fine finishing of hardwood floors
- Large non-marking transport wheels
- Precision balanced for smooth operation
- Available in standard or dust control version
- Excellent “between coats” system

### SPECIFICATIONS

	OBS 18	OBS 18DC
Part Number	07076B	07081B
Sanding Path	18 in. (45.7 cm)	
Sanding Pad Size	12 x 18 in. (30.5 x 45.7 cm)	
Motor	1 HP	
Voltage	115V/60 Hz	
Power Cable (14-3 grey)	50 ft. (15.2 m)	
Speed of Sanding Pad (AC)	3600 orbits per minute	
Noise Level	74 dB(A)	
Dimensions (L x W x H)	18.5 x 20 x 45 in. (46.9 x 50.8 x 114.3 cm)	
Weight	125 lbs. (56.7 kg)	
Shipping Weight	145 lbs. (65.8 kg)	
Warranty	One Year Parts & Labor	

## Pride PROGRAM

We believe in our products and our people.  
That's why we created the PRIDE PROGRAM:

- A 60-day satisfaction guarantee on our machines
- A chance to win a free edger by returning the product's registration card
- Communication with us through our Quality Management System



Dust Skirt Assembly  
For OBS 18DC  
PN 18455A

### PRODUCT

- Seamless chrome handle tube resists rust, and increases durability.
- Totally enclosed fan cooled dual capacitor motor eliminates overheating
- Heavy cast iron main frame supplies weight for aggressive performance
- Cast aluminum pad driver plate reduces chance of bending
- Unique skirting directs air to pick-up chamber (DC only)
- Large 9 inch vacuum fan eliminates annoying dust (DC only)
- Large 1 1/8" diameter drive shaft resists damage

- Floating skirt requires no adjustment (DC only)
- Dual switch levers for easy operation with either hand
- Convenient lifting handle
- Dustless sanding reduces cleanup time (DC only)
- 3600 orbits per minute; sands and screens faster
- Precision balanced counter weight and oversized drive bearing supply consistent performance, while reducing vibration
- Ergonomic handle with safety interlock offers operator comfort and protection

### PRODUCTIVITY

- Designed specifically for the finishing and polishing of wood floors
- Large non-marking transport wheels protect finished areas from damage
- Full “harpoon” face pad driver effectively transfers motion to abrasive
- Small .25 in. orbit produces finer finish and reduces chance of swirl marks
- Cast pad driver keeps screens and paper flat on the floor

### SAFETY

- DC model controls dust for improved air quality
- Hospital grade plug assures electrical safety when connected to a properly grounded outlet

### EASE OF USE

- No side torque
- Operates in any direction

### Clarke®

2100 Hwy. 265  
Springdale, AR 72764

[www.americansanders.com](http://www.americansanders.com)

DISTRIBUTED BY:

Customer Service: 1.800.545.3454  
Fax Orders to: 1.800.825.2753  
Technical Service: 1.800.356.7274

©2005 ALTO U.S. Inc., All Rights Reserved. Specifications subject to change without notice. P/N 79703A Rev. 07/08

